APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/043,591	01/09/2002	Earl Vickers	2045.267US1	6349

21186   7590   04/27/2009
SCHWEGMAN, LUNDBERG & WOESSNER, P.A.
P.O. BOX 2938
MINNEAPOLIS, MN 55402

EXAMINER
LAO, LUN S

ART UNIT	PAPER NUMBER
2614	

MAIL DATE	DELIVERY MODE
04/27/2009	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
Office Action Summary	10/043,591	VICKERS ET AL.
	Examiner	Art Unit	
	LUN-SEE LAO	2614	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE <u>3</u> MONTH(S) OR THIRTY (30) DAYS,
WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed
  after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
  Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any
  earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☒ Responsive to communication(s) filed on <u>29 January 2009</u>.

2a)☐ This action is **FINAL.**   2b)☒ This action is non-final.

3)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is
closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4)☒ Claim(s) <u>1-8 and 11-21</u> is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5)☐ Claim(s) _____ is/are allowed.

6)☒ Claim(s) <u>1-8 and 11-21</u> is/are rejected.

7)☐ Claim(s) _____ is/are objected to.

8)☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9)☐ The specification is objected to by the Examiner.

10)☐ The drawing(s) filed on _____ is/are: a)☐ accepted or b)☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a)☐ All   b)☐ Some * c)☐ None of:

      1.☐ Certified copies of the priority documents have been received.

      2.☐ Certified copies of the priority documents have been received in Application No. _____.

      3.☐ Copies of the certified copies of the priority documents have been received in this National Stage
        application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1)☒ Notice of References Cited (PTO-892)

2)☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3)☐ Information Disclosure Statement(s) (PTO/SB/08)
    Paper No(s)/Mail Date _____.

4)☐ Interview Summary (PTO-413)
    Paper No(s)/Mail Date. _____.

5)☐ Notice of Informal Patent Application

6)☐ Other: _____.

DETAILED ACTION

Introduction

1.   This action is in response to the amendments filed on 01-29-2009.

Claims 1, 4, 5, 7, 8, 11, 12, 14, 18 and 20 have been amended and claims 9 and 10

have been canceled. Claims 1 - 8 and 11 - 21 are pending.

Continued Examination Under 37 CFR 1.114

2.   A request for continued examination under 37 CFR 1.114, including the fee set forth

in 37 CFR 1.17(e), was filed in this application after final rejection. Since this

application is eligible for continued examination under 37 CFR 1.114, and the fee set

forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action

has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 03-02-

2009 has been entered.

Drawings

3. The drawings are objected to under 37 CFR 1.83(a). The drawings must show every

feature of the invention specified in the claims. Therefore, the "deriving at least two

parameters of a transfer function from a statistical distribution of levels encountered

over all frames of the audio track; deriving, from the transfer function, a time-varying

gain to modify the statistical distribution of levels of the audio track; and applying the

time-varying gain to the audio track to obtain a resulting audio track, wherein the

transfer function comprises a multi-line compression transfer function having one or

more compression thresholds, and wherein the parameters include the one or more

compression thresholds that are derived from <u>a fractional measure of a number of the</u> <u>frames measured over all the frames of the audio track at one or more predetermined</u> <u>levels</u>" must be shown or the feature(s) canceled from the claim(s). No new matter should be entered.

Corrected drawing sheets in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. Any amended replacement drawing sheet should include all of the figures appearing on the immediate prior version of the sheet, even if only one figure is being amended. The figure or figure number of an amended drawing should not be labeled as "amended." If a drawing figure is to be canceled, the appropriate figure must be removed from the replacement sheet, and where necessary, the remaining figures must be renumbered and appropriate changes made to the brief description of the several views of the drawings for consistency. Additional replacement sheets may be necessary to show the renumbering of the remaining figures. Each drawing sheet submitted after the filing date of an application must be labeled in the top margin as either "Replacement Sheet" or "New Sheet" pursuant to 37 CFR 1.121(d). If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

Claim Rejections - 35 USC § 112

4.   Claims 1, 14, 18, and 20 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject

matter which was not described in the specification in such a way as to reasonably

convey to one skilled in the relevant art that the inventor(s), at the time the application

was filed, had possession of the claimed invention. The claim1 limitation as recited "

deriving at least two parameters of a transfer function from a statistical distribution of

levels encountered over all frames of the audio track; deriving, from the transfer

function, a time-varying gain to modify the statistical distribution of levels of the audio

track; and applying the time-varying gain to the audio track to obtain a resulting audio

track, wherein the transfer function comprises a multi-line compression transfer function

having one or more compression thresholds, and wherein the parameters include the

one or more compression thresholds that are derived from a fractional measure of a

number of the frames measured over all the frames of the audio track at one or more

predetermined levels". However, the specification does not clearly disclose that "the

parameters include the one or more compression thresholds that are derived from a

fractional measure of a number of the frames measured over all the frames of the audio

track at one or more predetermined levels" will be performed. The applicant pointed the

added limitation support by specification in paragraph [0034]. In paragraph [0034] only

discloses the loudness of a signal may be calculated by determining an average level

for all of the frames comprising the audio track. Similarly, the loudness of an audio

signal may be calculated by taking an average level for a set of the loudest frames

comprising the audio track, since it is believed that the loudest frames contribute the

most to the perception of overall loudness.   It is not supported in the specification nor in

any claim originary presented and any figures.

Consider claims 14, 18 and 20 they are essentially similar to claim 1 and are rejected

for the reason stated above apropos to claim 1.

5.   Claim 4 is rejected under 35 U.S.C. 112, first paragraph, as failing to comply with

the written description requirement. The claim(s) contains subject matter which was not

described in the specification in such a way as to reasonably convey to one skilled in

the relevant art that the inventor(s), at the time the application was filed, had possession

of the claimed invention. The claimed limitation as recited in claim 4 " the step of

deriving the time varying gain comprises: deriving, from histogram data of levels

encountered in the audio track, an original dynamic spread value representing a spread

of the levels encountered over all the frames in the audio track; performing a

comparison between the original dynamic spread value and a desired dynamic spread

value; and deriving a parameter for the transfer function from the comparison".

However, the specification does not clearly disclose that "the step of deriving the time

varying gain comprises: deriving, from histogram data of levels encountered in the audio

track, an original dynamic spread value representing a spread of the levels encountered

over all the frames in the audio track" will be performed. The applicant pointed the

added limitation support by specification in paragraph [0034]. In paragraph [0034] only

discloses the loudness of a signal may be calculated by determining an average level

for all of the frames comprising the audio track. Similarly, the loudness of an audio

signal may be calculated by taking an average level for a set of the loudest frames

comprising the audio track, since it is believed that the loudest frames contribute the

most to the perception of overall loudness.   It is not supported in the specification nor in

any claim originary presented and any figures.

Claim Rejections - 35 USC § 103

6.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set
> forth in section 102 of this title, if the differences between the subject matter sought to be patented and
> the prior art are such that the subject matter as a whole would have been obvious at the time the
> invention was made to a person having ordinary skill in the art to which said subject matter pertains.
> Patentability shall not be negatived by the manner in which the invention was made.

7.   Claims 1-3, 5 and 14-21 are rejected under 35 U.S.C. 103(a) as being

unpatentable over Saunders (US PAT. 6,351,733) in view of Cellier (US PAT.

5,884,269).

   Regarding Claim 1 Saunders discloses a method of adjusting the dynamics of an

audio track, comprising:

   deriving, from the transfer function (reads on VRA function), a time-varying gain to

modify the statistical distribution of levels of the audio track (see Figs. 1, 5, and 13-14;

column 17, line 16 to column 18, line 34; column 23, lines 57-67); and

   applying the time-varying gain to the audio track to obtain a resulting audio track,

wherein the transfer function comprises a multi-line compression transfer function

(reads on, PCPV/PCA and/or SCRA) having one or more compression thresholds

(reads on, 8:1), and wherein the parameters include the one or more compression

thresholds that are derived on from a fractional measure of the audio track at one or

more predetermined levels (see Figs. 1, 5, and 13-14; and see column 13, line 8 to

column 14, line 10; column 17, line 16 to column 18, line 34; column 23, lines 48-67);

but Saunder does not explicitly teach deriving at least two parameters of a transfer

function from a statistical distribution of levels encountered over all frames of the audio

track; and wherein the parameters include the one or more compression thresholds that

are derived from a fractional measure of a number of the frames measured over all the

frames of the audio track at one or more predetermined levels.

However, Cellier teaches that deriving at least two parameters of a transfer function

from a statistical distribution of levels encountered over all frames of the audio track(see

col. 3 line 35-col. 4 line 67); and wherein the parameters include the one or more

compression thresholds that are derived from a fractional measure of a number of the

frames measured over all the frames of the audio track at one or more predetermined

levels (see figs 1-5 and col.5 line 23-col. 6 line 67).

Therefore, it would have been obvious to one of ordinary skill in the art at the time

the invention was made to combine the teaching of Cellier into Saunders to provide

a highly efficient and compact way of mapping the statistics of actual audio signal for

the sound system.

Regarding Claim 2, Saunders discloses that the step of deriving the transfer

function comprises:

specifying a desired statistical dynamics distribution (Figs. 1 and 13-14; column 17,

line 16 to column 18, line 34; column 23, lines 57-67; column 22, lines 53-60); and

deriving the parameters (see col. 10 line 2-20) of the transfer function (reads on, wave

form in each channel) from the metadata and from the desired statistical dynamics

distribution (Figs. 13-14; column 17, line 16 to column 18, line 34; column 23, lines 48-

67; column 22, lines 53-60); such that a final statistical dynamics distribution

encountered in the resulting audio track after application of the time-varying gain is

substantially similar to the desired statistical dynamics distribution (Figs. 1 and 13-14;

column 17, line 16 to column 18, line 34; column 23, lines 48-67).

   Regarding Claim 3, Saunders discloses deriving the time varying gain comprises:

specifying a desired overall loudness for the audio track (Figs. 1 and 13-14; column 17,

line 16 to column 18, line 34; column 23, lines 57-67; column 22, lines 53-67) deriving

an estimate of the loudness of the resulting audio track from the metadata and from an

initial estimate of the time-varying gain (Figs. 1 and 13-14; column 17, line 16 to column

18, line 34; column 23, lines 57-67; column 22, lines 53-67); deriving a correction factor

from the desired overall loudness and from the estimate of the loudness of the resulting

audio track (Figs. 1-5 and 13-14; column 17, line 16 to column 18, line 34; column 23,

lines 57-67; column 22, lines 53-67; column 23, line 48 to column 24, line 6); and

applying the correction factor to the initial estimate of the time-varying gain to obtain the

time-varying gain (Figs. 1 and 13-14; column 17, line 16 to column 18, line 34; column

23, lines 57-67; column 22, lines 53-67; column 23, line 48 to column 24, line 6; column

26, line 40 to column 27, line 4).

   Regarding Claim 5, Saunders as modified by Cellier discloses the step of deriving

parameters comprises: determining a slope of a segment of a the multi-line compressor

transfer function; and determining a threshold between two segments of the multi-line

compressor transfer function (in Cellier, see figs 1-5 and col.5 line 23-col. 6 line 67).

Regarding Claim 14, Saunders discloses a method of adjusting the loudness of an

audio track including a plurality of audio frames, the method comprising:

obtaining loudness values for each of the plurality of audio frames (Figs. 1, 5, and

13-14; column 17, line 16 to column 18, line 34);

applying a weighting factor (see fig.13 (11340) and see col.22 line 53-col. 23 line 67)

to each of the loudness values to obtain a plurality of weighted loudness values (Figs. 1,

5, and 13-14; column 17, line 16 to column 18, line 34);

aggregating the weighted loudness values (see fig.13 (multiplier)) to obtained an

overall loudness value for the audio track (Figs. 1, 5, and 13-14; column 17, line 16 to

column 18, line 34; column 23, lines 48-67);

comparing the overall loudness value (see col. 17 line 46-67) to a desired loudness

value (Figs. 1, 5, and 13-14; column 17, line 16 to column 18, line 34; column 23, lines

48-67; column 22, lines 53-60; column 26, line 40 to column 4); and

applying a gain (see fig.13, (1340)) to the audio track based on the comparison

between the overall loudness value and the desired loudness value (Figs. 1, 5, and 13-

14; column 17, line 16 to column 18, line 34; column 23, lines 48-67; column 22, lines

53-60; column 26, line 40 to column 4); wherein applying the gain comprises

compressing with a multi-line compression transfer function derived from statistical

frequency data, the multi-line compression transfer function(reads on, PCPV/PCA

and/or SCRA) including one or more compression thresholds (reads on, 8:1) that are

derived from a fractional measure of the audio track at one or more predetermined

levels (see Figs. 1, 5, and 13-14; and see column 13, line 8 to column 14, line 10;

column 17, line 16 to column 18, line 34; column 23, lines 48-67); but Saunders does

not explicitly teach the multi-line compression transfer function including one or more

compression thresholds that are derived from a fractional measure of a number of the

frames measured over all the frames of the audio track at one or more predetermined

levels.

However Cellier teaches that applying the gain comprises compressing with a multi-

line compression transfer function derived from statistical frequency data, the multi-line

compression transfer function including one or more compression thresholds that are

derived from a fractional measure of a number of the frames measured over all the

frames of the audio track at one or more predetermined levels (see figs 1-5 and col. 3

line 35-col. 4 line 67 and col.5 line 23-col. 6 line 67).

Therefore, it would have been obvious to one of ordinary skill in the art at the time

the invention was made to combine the teaching of Cellier into Saunders to provide

a highly efficient and compact way of mapping the statistics of actual audio signal for

the sound system.

Regarding Claim 15, Saunders discloses the weighting factor to be applied to a

particular loudness value is derived from the particular loudness value itself (Figs. 1, 5,

and 13-14; column 17, line 16 to column 18, line 34; column 23, lines 48-67; column 22,

lines 53-60; column 26, line 40 to column 4).

Regarding Claim 16, Saunders discloses the weighting factor for a particular

loudness value comprises an emphasis parameter raised to a power of the particular

loudness value (Figs. 1, 5, and 13-14; column 17, line 16 to column 18, line 34; column

23, lines 48-67; column 22, lines 53-60; column 26, line 40 to column 4).

Regarding Claim 18, Saunders discloses a method of altering a dynamic range of an

audio track comprising a plurality of audio frames each having a loudness value, the

method comprising: obtaining original statistical frequency data for the audio track (Figs.

1, 5, and 13-14; column 17, line 16 to column 18, line 34); applying a test compression

scheme to the original statistical frequency data to obtain test statistical frequency data

(Figs. 1,2A-2B, 3, 5, and 13-14; column 17, line 16 to column 18, line 34); deriving from

the original statistical frequency data and the test statistical frequency data an actual

compression scheme (Figs. 1, 2A-2B, 3, 5, and 13-14; column 17, line 16 to column 18,

line 34); and compressing the audio track using the actual compression scheme (Figs.

1, 2A-2B, 3, 5, and 13-14; column 17, line 16 to column 18, line 34); wherein

compressing using the actual compression scheme comprises compressing with a

multi-line compression transfer function(reads on PCPV/PCA and/or SCRA)

derived from the statistical frequency data, the multi- line compression transfer function

including one or more compression thresholds (reads 8:1) that are derived from a

fractional measure of the audio track at one or more predetermined levels (see Figs. 1,

5, and 13-14; and see column 13, line 8 to column 14, line 10; column 17, line 16 to

column 18, line 34; column 23, lines 48-67); but Saunders does not explicitly teach

obtaining original statistical frequency data for the audio track, the original statistical frequency data comprising a statistical distribution of levels encountered over all frames of the audio track; and the multi- line compression transfer function including one or more compression thresholds that are derived from a fractional measure of a number of the frames measured over all the frames of the audio track at one or more predetermined levels.

However, Cellier teaches that obtaining original statistical frequency data for the audio track, the original statistical frequency data comprising a statistical distribution of levels encountered over all frames of the audio track(see col. 3 line 35-col. 4 line 67); and compressing the audio track using the actual compression scheme, wherein compressing using the actual compression scheme comprises compressing with a multi-line compression transfer function derived from the statistical frequency data, the multi- line compression transfer function including one or more compression thresholds that are derived from a fractional measure of a number of the frames measured over all the frames of the audio track at one or more predetermined levels(see figs 1-5 and col.5 line 23-col. 6 line 67).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to combine the teaching of Cellier into Saunders to provide a highly efficient and compact way of mapping the statistics of actual audio signal for the sound system.

Regarding Claim 19, Saunders discloses obtaining a mean loudness deviation value from the loudness values for the plurality of audio frames; determining a test mean

loudness deviation value from the test statistical frequency data; and comparing the

mean loudness deviation value and the test mean loudness deviation value with a

desired mean loudness deviation value when deriving the actual compression scheme

(Figs. 1,2A-2B, 3, 5, and 13-14; column 17, line 16 to column 18, line 34).

Regarding Claim 20, Saunders discloses a method of processing an audio track

comprising: obtaining statistical frequency data for the audio track (Figs. 1, 5, and 13-

14; column 17, line 16 to column 18, line 34); applying a compression scheme to the

statistical frequency data to obtain an estimate of statistical frequency data that would

result from applying the compression scheme directly to the audio track (Figs. 1, 2A-2B,

3, 5, and 13-14; column 8, line 7 to column 9, line 51; column 17, line 16 to column 18,

line 34); determining an estimated overall compressed loudness value from the estimate

of statistical frequency data (Figs. 1, 2A-2B, 3, 5, and 13-14; column 17, line 16 to

column 18, line 34); compressing the audio track using the compression scheme to

obtain a compressed audio track (Figs. 1, 2A-2B, 3, 5, and 13-14; column 17, line 16 to

column 18, line 34); and applying a gain to the compressed audio track based on a

comparison between the estimated overall compressed loudness value and a desired

loudness value (Figs. 1, 2A-2B, 3, 5, and 13-14; column 17, line 16 to column 18, line

34); wherein compressing using the compression scheme comprises compressing with

a multi- line compression transfer function (reads on PCPV/PCA and/or SCRA)

derived from the statistical frequency data, the compression transfer function including

one or more compression thresholds (reads on, 8:1) that are derived from a fractional

measure of the audio track at one or more predetermined levels (see Figs. 1, 5, and

13-14; and see column 13, line 8 to column 14, line 10; column 17, line 16 to column 18, line 34; column 23, lines 48-67); but Saunders does not explicitly teach obtaining original statistical frequency data for the audio track, the original statistical frequency data comprising a statistical distribution of levels encountered over all frames of the audio track; and the multi- line compression transfer function including one or more compression thresholds that are derived from a fractional measure of a number of the frames measured over all the frames of the audio track at one or more predetermined levels.

However, Cellier teaches that obtaining original statistical frequency data for the audio track, the original statistical frequency data comprising a statistical distribution of levels encountered over all frames of the audio track(see col. 3 line 35-col. 4 line 67); and compressing the audio track using the actual compression scheme, wherein compressing using the actual compression scheme comprises compressing with a multi-line compression transfer function derived from the statistical frequency data, the multi- line compression transfer function including one or more compression thresholds that are derived from a fractional measure of a number of the frames measured over all the frames of the audio track at one or more predetermined levels(see figs 1-5 and col.5 line 23-col. 6 line 67).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to combine the teaching of Cellier into Saunders to provide a highly efficient and compact way of mapping the statistics of actual audio signal for the sound system.

Regarding Claim 21, Saunders discloses the overall compressed loudness value is
obtained by: obtaining a plurality of individual loudness values from the estimate of
statistical frequency data; applying a weighting factor to each of the individual loudness
values to obtain weighted loudness values; and aggregating the weighted loudness
values to obtained the overall compressed loudness value for the audio track (Figs. 1,
2A-2B, 3, 5, and 13-14; column 8, line 7 to column 9, line 51; column 17, line 16 to
column 18, line 34; column 23, lines 48-67; column 22, lines 53-60; column 26, line 40
to column 4).

Regarding Claim 17, Saunders discloses a metadata which is the audio control
information, but does not expressly disclose the weighted loudness values of the
plurality of audio frames are aggregated using a histogram (column 7, line 42 to column
8, line 60). However, the examiner takes Official Notices that it well known in the art to
provide metadata comprises histogram associated with the audio control information in
order to further enhance the playback features available. Therefore it would have been
obvious to one having ordinary skill in the art at the time the invention was made to
modify Saunders to have the metadata of Saunders, comprise histogram associated
with the audio control information in order to further enhance the playback features
available.

8.   Claims 4, 11 and 12 are rejected under 35 U.S.C. 103(a) as being unpatentable
over Saunders (US PAT. 6,351,733) as modified by Cellier (US PAT. 5,884,269)

as applied to claims 1-3 above, and further in view of Kashino et al. (US PAT.

6,826,350).

   Regarding 4, Saunders as modified by Cellier does not explicitly teach

the step of deriving the time varying gain comprises: deriving, from histogram data of

levels encountered in the audio track, an original dynamic spread value representing a

spread of the levels encountered over all the frames in the audio track; performing a

comparison between the original dynamic spread value and a desired dynamic spread

value; and deriving a parameter for the transfer function from the comparison.

   However, Kashino discloses deriving, from histogram data of levels encountered in

the audio track, an original dynamic spread value representing a spread of the levels

encountered over all the frames in the audio track; performing a comparison between

the original dynamic spread value and a desired dynamic spread value; and deriving a

parameter for the transfer function from the comparison(see figs 4-9 and col. 10 line 7-

col. 11 line 65).

   Therefore, it would have been obvious to one of ordinary skill in the art at the time

the invention was made to combine the teaching of Kashino into Saunders and Cellier

to provide a high speed signal search for audio system.

   Regarding Claim 11, Saunders as modified by Cellier teaches the parameters include

a level of a threshold separating two segments of a the multi-line compressor transfer

function(in Cellier, see figs 1-5 and col.5 line 23-col. 6 line 67).

Regarding Claim 12, Saunders as modified by Cellier teaches specifying a fraction representing a proportion of the audio track to which compression will be applied; and using the loudness value as a threshold separating two segments of a the multi-line compressor transfer function(in Cellier, see figs 1-5 and col.5 line 23-col. 6 line 67); but Saunders as modified by Cellier does not explicitly teach deriving from the histogram data a loudness value corresponding to a point above or below which the fraction of the histogram data is located.

However, Kashino deriving from the histogram data a loudness value corresponding to a point above or below which the fraction of the histogram data is located (see figs 4-9 and col. 10 line 7-col. 11 line 65).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to combine the teaching of Kashino into Saunders and Cellier to provide a high speed signal search for audio system.

9.　　Claim 6-8 and 13 are rejected under 35 U.S.C. 103(a) as being unpatentable over Saunders (US PAT. 6,351,733) as modified by Cellier (US PAT. 5,884,269) as applied to claims 1 and 5 above, and further in view of Nakano (US PAT. 5,404,315).

Regarding 6, Saunders as modified by Cellier does not explicitly teach determining the slope comprises: applying a test compression scheme to the histogram data to obtain test histogram data, the test compression scheme including a test slope; determining a test dynamic spread value from the test histogram data; and deriving the

slope based on a comparison of the original dynamic spread value, the desired dynamic

spread value and the test dynamic spread value.

However, Nakano discloses determining the slope comprises: applying a test

compression scheme to the histogram data to obtain test histogram data, the test

compression scheme including a test slope (Figs. 1, 7-10; column 7, lines 42-51);

determining a test dynamic spread value from the test histogram data (column 7, line 42

to column 8, line 60); and deriving the slope based on a comparison of the original

dynamic spread value, the desired dynamic spread value and the test dynamic spread

value (column 6, lines 5-27).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the

invention was made to combine the teaching of Nakano into Saunders and Cellier to

provide better gain control for enhancing the audio output to the user.

Regarding Claims 7-8, Saunders as modified by Cellier and Nakano teaches the

slope for segments of the multi-line compressor transfer function is determined using

interpolation(in Cellier, see figs 1-5 and col.5 line 23-col. 6 line 67); and the slope for

segments of the multi-line compressor transfer function is determined using iteration

(in Cellier, see figs 1-5 and col.5 line 23-col. 6 line 67).

Regarding Claim 13, Nakano discloses deriving a test overall loudness value from

the test histogram data; deriving a fixed post-gain value from the test overall loudness

value and from a desired loudness value; and applying the time varying gain and the

fixed post-gain value to the audio track (Figs. 1, 7-10; column 6, lines 5-27; column 7,

line 42 to column 8, line 60). Note the discussion of claim 6 for a motivation to combine.

Response to Arguments

10. Applicant's arguments with respect to claims 1-21 have been considered but are

moot in view of the new ground(s) of rejection.

Conclusion

11.   The prior art made of record and not relied upon is considered pertinent to

applicant's disclosure.

12.   Any response to this action should be mailed to:

Mail Stop ____(explanation, e.g., Amendment or After-final, etc.)

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450
Facsimile responses should be faxed to:
(571) 273-8300
Hand-delivered responses should be brought to:
Customer Service Window
Randolph Building
401 Dulany Street
Alexandria, VA 22314

Any inquiry concerning this communication or earlier communications from the examiner

should be directed to Lao, Lun-See whose telephone number is (571) 272-7501 The examiner

can normally be reached on Monday-Friday from 8:00 to 5:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Vivian Chin, can be reached on (571) 272-7848.

Any inquiry of a general nature or relating to the status of this application or proceeding

should be directed to the Technology Center 2600 whose telephone number is (571) 272-2600.

Lao, Lun-See
/LUN-SEE LAO/
Examiner, Art Unit 2614
Patent Examiner
US Patent and Trademark Office
Knox
571-272-7501
Date 04-24-2009

/Vivian Chin/

Supervisory Patent Examiner, Art Unit 2614